



Material		Stainless steel pipe (SUS316TP-A) Equivalent to JIS standard number G3459									
Standard		Pipe nipple (threaded pipe fittings JIS B 2302) Screw: PT (tapered pipe thread JIS B 0203)									
Shape		 Double screw  Single screw									
Diameter	Length	Short nipple	50mm	65mm	75mm	100mm	125mm	150mm	200mm	250mm	300mm
6A	1/8B	\$4.09 1200 (100×12)	\$5.09 600 (100×6)	\$6.27 600 (100×6)	\$7 500 (100×5)	\$8.18 400 (100×4)	\$10.36 300 (50×6)	\$11.18 250 (50×5)	\$13.91 200 (50×4)	OpenPrice BTO	OpenPrice BTO
8A	1/4B	\$4.09 1200 (100×12)	\$5.09 600 (100×6)	\$6.27 600 (100×6)	\$7 500 (100×5)	\$8.18 400 (100×4)	\$10.36 300 (50×6)	\$11.18 250 (50×5)	\$13.91 200 (50×4)	OpenPrice BTO	OpenPrice BTO
10A	3/8B	\$4.09 800 (100×8)	\$5.09 400 (100×4)	\$6.27 400 (100×4)	\$7 300 (100×3)	\$8.18 250 (50×5)	\$10.36 200 (50×4)	\$11.18 150 (50×3)	\$13.91 150 (50×3)	OpenPrice BTO	OpenPrice BTO
15A	1/2B	\$5.09 400 (50×8)	\$7 300 (50×6)	\$7.45 200 (50×4)	\$8.18 200 (50×4)	\$9.45 150 (50×3)	\$12.91 100 (50×2)	\$14.09 100 (50×2)	\$17.64 100 (50×2)	OpenPrice BTO	OpenPrice BTO
20A	3/4B	\$5.82 300 (50×6)	\$7.45 200 (50×4)	\$8.64 200 (50×4)	\$9.27 150 (50×3)	\$11.27 100 (50×2)	\$14.09 80	\$16.82 80	\$20.45 60	OpenPrice BTO	OpenPrice BTO
25A	1B	\$8 200	\$8.91 200	\$10.55 170	\$11.64 140	\$14.18 100	\$17.73 80	\$20.45 70	\$25.36 50	OpenPrice BTO	OpenPrice BTO
32A	1 1/4B	\$11.27 100		\$13.91 85	\$15.73 85	\$19.27 60	\$24.18 45	\$28.09 40	\$34.45 30	OpenPrice BTO	OpenPrice BTO
40A	1 1/2B	\$12.45 80		\$15.27 60	\$17.55 60	\$21.55 45	\$26.55 35	\$29.82 30	\$38.73 20	OpenPrice BTO	OpenPrice BTO
50A	2B	\$18 55		\$20.09 40	\$22.36 40	\$27.09 30	\$33.45 20	\$38.82 20	\$47.64 15	OpenPrice BTO	OpenPrice BTO
65A	2 1/2B	\$32.91 24				\$50.55 18	\$61 15	\$70.64 12	\$89.73 9	OpenPrice BTO	OpenPrice BTO
80A	3B	\$43.09 18				\$62.18 12	\$74.64 9	\$87 9	\$109.45 6	OpenPrice BTO	OpenPrice BTO
100A	4B	\$81.09 6				\$95.45 6	\$110.18 5	\$149.27 5	\$157.36 3	OpenPrice BTO	OpenPrice BTO

※ Prices in parentheses are for large boxes and small boxes.

#### ▼ Summary

This is a pipe fitting of the external thread type that requires a tapered male thread (nominal: R or PT).

#### ▼ Main applications

Indoor fire hydrant piping, indoor sprinkler system piping and foam extinguishing piping, general gas piping, general air piping or general air conditioning piping to distribute pressurized air from compressors, etc. to various facilities, piping for the flow of fluid to various machines and equipment or covered piping to protect structural parts, wiring, etc., and structural members such as handrails and plumbing.

#### ▼ Recommended Pressure

Airtightness: 0.5MPa (approx. 5kgf/cm<sup>2</sup>) or less

Pressure resistance: Less than 2.5MPa (approx. 25kgf/cm<sup>2</sup>)

#### ▼ Features of tapered pipe screws (JIS B 0203)

These screws are mainly used to ensure tightness in the threaded parts of pipes, pipe components and fluid equipment. The screw is shaped like a figure of eight with an angle of about 3.6 degrees from the tip of the screw to the end of the screw, with the tip of the screw being the thinnest and the end of the screw being the thickest. As you tighten the screw, the threads gradually intersect with those of the mating threads, and when the final torque is applied, the threads interlock with each other to close the gap between the inside and outside of the pipe, ensuring an airtight seal. Unlike a straight threaded screw, once the screw is torqued down, the threads are worn out the next time it is loosened. It is not suitable for use in areas where the screw is re-tightened many times.

#### ▼ Inspection of Screws

All inspections of the screws are performed using tapered thread gauges that are specified in JIS B0253, the standard number of the Japanese Industrial Standard (JIS). (We use OSG gauges manufactured by OSG as the inspection gauge manufacturer.)

#### ▼ Chemical Composition

Type	Symbol	Chemical composition (%)							
		C	Si	Mn	P	S	Ni	Cr	Mo
SUS316	SUS316TP	0.08 or less	0.1 or less	2.0 or less	0.045 or less	0.03 or less	10.0 to 14.0	16.0 to 18.0	2 to 13